



The Model T102 UV Fluorescence TRS Analyzer



The Model T102 TRS analyzer uses the proven UV fluorescence principle to measure Total Reduced Sulfur at levels commonly required for ambient air monitoring.

— Available with NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty



T102 Specifications

■ Ranges	TRS Min: 0 - 50 ppb full scale Max 0-10 ppm full scale SO ₂ Up to 0-20 ppm full scale (selectable, independent and dual range supported)
■ Measurement Units	ppb, ppm, µg/m ³ , mg/m ³ (selectable)
■ Zero Noise	< 0.2 ppb (RMS)
■ Span Noise	< 0.5% of reading (RMS) above 50 ppb
■ Lower Detectable Limit	0.4 ppb
■ Zero Drift	< 0.5 ppb/24 hours
■ Span Drift	< 0.5% of full scale/24 hours
■ Lag Time	20 seconds
■ Rise/Fall Time	< 20 seconds to 95%
■ Linearity	1% of full scale
■ Precision	0.5% of reading above 50 ppb
■ Sample Flow Rate	650 cc/min ±10%
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	±10%
■ Included I/O	1 x Ethernet: 10/100 Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4 - 20mA current outputs
■ Operating Temperature Range	5 - 40°C (with US EPA Approval) 850° C (external converter)
■ Dimensions (HxWxD)	Analyzer 7" x 17" x 23.5" (178 x 432 x 597 mm) Converter: 7" x 17" x 23.5"
■ Weight	Analyzer 37 lbs (16.8 kg) Converter: 16 lbs (7.3kg) Converter: 26 lbs (11.8kg) CE version

* All certifications apply for legacy or NumaView™ T Series analyzer software

NumaView™ software is available as a no-charge option that must be specified at the time of purchase.

Specifications subject to change without notice. *
All Specifications are based on constant conditions



TELEDYNE API
Everywhere you look™

9970 Carroll Canyon Road ■ San Diego, CA 92131
Ph. 858-657-9800 Fax 858-657-9816
Email api-sales@teledyne.com

For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2017 Teledyne API
Printed documents are uncontrolled. SAL000043B (DCN 7538) 03.13.17

