

The Model T300 Gas Filter Correlation CO Analyzer



Using IR Gas Filter Correlation technology, the Model T300 CO analyzer produces excellent zero and span stability, high signal-to-noise ratio, and provides advanced electronics to allow accurate, dependable, continuous measurements for ambient air quality, stack gas monitoring and other applications.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty and five years on the GFC wheel





T300 Specifications

| Ranges | Min: 0 - 1 ppm full scale Max: 0 - 1,000 ppm full scale (selectable, dual-range supported) |
|-----------------------------|---|
| Measurement Units | ppb, ppm, μg/m ³ , mg/m ³ (selectable) |
| Zero Noise | < 0.02 ppm (RMS) |
| Span Noise | < 0.5% of reading (RMS) above 5 ppm |
| Lower Detectable Limit | 0.04 ppm |
| Zero Drift | < 0.1 ppm/24 hours |
| Span Drift | < 0.5% of reading/24 hours |
| Lag Time | 10 seconds |
| Rise/Fall Time | < 60 seconds to 95% |
| Linearity | 1% of full scale |
| Precision | 0.5% of reading (RMS) above 5 ppm |
| Sample Flow Rate | 800 cc/min ±10% |
| Power Requirements | 100V-120V, 220V-240V, 50/60 Hz |
| Analog Output Ranges | 10V, 5V, 1V, 0.1V (selectable) |
| Recorder Offset | ±10% |
| Included I/O | 1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs |
| Optional I/O | 1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs |
| Operating Temperature Range | 5 - 40°C operating, 10 - 40°C (US EPA Equivalency) |
| Dimensions (HxWxD) | 7" x 17" x 23.5" (178 x 432 x 597 mm) |
| Weight | 40 lbs (18 kg) |
| Certifications | US EPA: RFCA-1093-093 EU: EN14626 TÜV Rheinland QAL1 Certified: EN15267 MCerts: Sira MC050069/07 CNEMC: 质(认)字 No. 2015-028 Report |

Specifications subject to change without notice.

All specifications are based on constant conditions.



9970 Carroll Canyon Road • San Diego, CA 92131 Ph. 858-657-9800 Fax 858-657-9816 Email api-sales@teledyne.com For more information about the Teledyne API family of monitoring instrumentation products, call us or visit our website at:

www.teledyne-api.com

© 2018 Teledyne API Printed documents are uncontrolled. SAL000053G (DCN 7833) 02.09.18

